


POMPA TIPO Pump type	gr.	Dimensioni costruttive Construction dimensions													
		DNa	DNm	a	h1	h2	b	c	m1	m2	n1	n2	s1	e1	e2
32-250	2	50	32	100	180	225	65	18	125	95	320	250	14	166	162
40-250	2	65	40	100	180	225	65	18	125	95	320	250	14	176	163
40-315	2	65	40	125	200	250	65	18	125	95	345	280	14	205	200
50-250	2	80	50	125	180	225	65	18	125	95	320	250	14	183	169
50-315	2	80	50	125	225	280	65	18	125	95	345	280	14	210	197
65-160	2	100	65	100	160	200	65	16	125	95	280	212	14	160	130
65-200	2	100	65	100	180	225	65	18	125	95	320	250	14	174	152
65-250	2	100	65	125	200	250	80	20	160	120	360	280	18	195	175
80-160	2	125	80	125	180	225	65	16	125	95	320	250	14	186	142
80-200	2	125	80	125	180	250	65	18	125	95	345	280	14	188	158
80-250	2	125	80	125	225	280	80	20	160	120	400	315	18	225	185
100-200	2	125	100	125	200	280	80	20	160	120	360	280	18	211	170
100-250	3	125	100	140	225	280	80	20	160	120	400	315	18	215	183
125-250	3	150	125	140	250	355	80	20	160	120	400	315	18	245	200
150-250	3	200	150	160	280	375	100	22	200	150	500	400	22	300	240

Dimensioni flange Flanges dimensions				
DNa-DNm	D	K	F	N° fori holes
32	140	100	18	4
40	150	110	18	4
50	165	125	18	4
65	185	145	18	4
80	200	160	18	8
100	220	180	18	8
125	250	210	18	8
150	285	240	22	8
200	340	295	22	12



POMPA TIPO Pump type	motore motor 180						motore motor 200				
	gr.	p	G1	h3	h4	Peso Weight	p	G1	h3	h4	Peso Weight
32-250	2	251.5	372.5	-	-	72.5	275.5	408.5	20	-	89.5
40-250	2	253	374	-	-	73.5	277	410	20	-	88.5
40-315	2	251.5	372.5	-	20	89	275.5	408.5	-	-	108.5
50-250	2	251.5	372.5	-	-	76	275.5	408.5	20	-	92.5
50-315	2	251.5	372.5	-	45	95	275.5	408.5	-	25	112.5
65-160	2	253	374	20	-	62.5	277	410	40	-	75.5
65-200	2	253	374	-	-	69.5	277	410	20	-	84
65-250	2	251.5	372.5	-	20	85.5	275.5	408.5	-	-	101
80-160	2	253	374	-	-	74	277	410	20	-	87.5
80-200	2	251.5	372.5	-	-	75.5	275.5	408.5	20	-	90
80-250	2	251.5	372.5	-	45	96.5	275.5	408.5	-	25	112
100-200	2	256	377	-	20	89	280	413	-	-	105

POMPA TIPO Pump type	motore motor 160					motore motor 180				motore motor 200			
	gr.	p	G1	h4	Peso Weight	p	G1	h4	Peso Weight	p	G1	h4*	Peso Weight
100-250	3	265	373	65	102	265	386	45	102	289	422	25	115.5
125-250	3	265	373	90	117.5	265	386	70	117.5	289	422	50	131
150-250	3	277	385	120	161.5	277	398	100	161.5	301	434	80	175

MOTORI ELETTRICI Electric Motors									
Grandezza Frame size IEC	Giri/min. RPM 1450		Giri/min. RPM 2900		Dimensioni costruttive Construction dimensions				
	kW	HP	kW	HP	Hm	A	B	C	F1
160 M	11	15	11-15	15-20	160	254	210	108	14
160 L	15	20	18.5	25		254	254	108	14
180 M	18.5	25	22	30	180	279	241	121	14
180 L	22	30	-	-		279	279	121	14
200 L	30	40	30-37	40-50	200	318	305	133	18

(h3-h4) Spessori per allineamento motore-pompa esclusi dalla fornitura.
 Raising pads for motor-pump alignment are not supplied by pompetravaini.

Disegno schematico. Dimensioni in mm con tolleranze secondo EN 735-1995.
 Pesì indicativi in Kg, riferiti a pompe in ghisa escluso motore, non impegnativi.
 Schematic drawing. Dimensions in mm with tolerances to EN 735-1995 standards.
 Weights in Kgs, referred to pumps in cast iron without motor, not certified.